

# A MID-RANGE CRANE

No matter what type of loads you move, there is a HIAB X-HiPro mid-range crane to match. Our offering covers a full range of loading capacities, and we tailor a solution that meets your requirements in every detail. Your choice of control system is only a start.



Technical data	HIAB X-HiPro 142	HIAB X-HiPro 162	HIAB X-HiPro 192
Lifting capacity (kNm)	131	150	178
Lifting capacity (tm)	13.3	15.3	18.1
Outreach, hydraulic extensions (m)	6.0-15.1	6.0-15.1	8.3-17.5
Installation space required, rotation area not included (mm)	817-963	878-969	865-985
Height in folded position (mm)	2236-2261	2261	2260-2265
Weight in standard version, without stabilisers (kg)	1580-2020	1710-2190	1935-2495
Weight, stabiliser equipment (kg)	244-385	244-385	271-428
<b>Features</b>			
nDurance	Standard	Standard	Standard
Base-mounted oil tank	Option	Option	Option
High seat	Option	Option	Option
Platform	Option	Option	Option
E-link	Standard	Standard	
E-link and X-feature			Standard
P-Boom			
Automatic Damping of Oil (ADO)	Standard	Standard	Standard
Automatic Duty Control (ADC)	Standard	Standard	Standard
Automatic Speed Control (ASC)			
Pump Flow Distribution (PFD)	Standard	Standard	Standard
Load Stability System Vertical (LSS-V)	Option	Option	Option
Load Stability System Horizontal (LSS-H)	Option	Option	Option
XSDrive remote control	Standard	Standard	Standard
XSDrive remote control Joystick	Option	Option	Option
CombiDrive remote control	Option	Option	Option
External Display	Option	Option	Option