



TS-JOY	1 LINK-J	BEHEW	RCL
			

BASICS
OPTIONS

MC														
	in	m	lbm	ft ³	mm	mm	mm	mm	mm	kg	kg	bar	l/min	kW
BDH-42	16.5	8.3	2426	400	2295	2500	885	5575	6455	1770	275	300	55	28
BDH-43	16.1	10.3	2426	400	2295	2500	885	5575	6455	1925	275	300	55	28
BDH-44	15.6	12.5	2426	400	2295	2500	885	5575	6455	2080	275	300	55	28
BDH-45	15.1	14.8	2426	400	2295	2500	885	5575	6455	2220	275	300	55	28
BDH-46	14.7	17.2	2426	400	2295	2500	885	5575	6455	2345	275	300	55	28
BDH-47	14.2	19.4	2426	400	2295	2500	995	5575	6455	2450	275	300	55	28
BDH-48	14.0	21.7	2426	400	2295	2500	995	5575	6455	2535	275	300	55	28

	HMF 80E-K2											
	kg	3830	▼	2620	▼	1980	▼					
	m	4,3	▼	6,2	▼	8,2	▼					
	HMF 80E-K3											
	kg	3660	▼	2470	▼	1840	▼	1460	▼			
	m	4,4	▼	6,3	▼	8,2	▼	10,2	▼			
	HMF 80E-K4											
	kg	3490	▼	2320	▼	1680	▼	1320	▼	1080	▼	
	m	4,5	▼	6,4	▼	8,3	▼	10,3	▼	12,4	▼	
	HMF 80E-K5											
	kg	3330	▼	2180	▼	1560	▼	1190	▼	950	▼	
	m	4,6	▼	6,4	▼	8,4	▼	10,4	▼	12,5	▼	
	HMF 80E-K6											
	kg	3170	▼	2050	▼	1430	▼	1060	▼	830	▼	
	m	4,6	▼	6,5	▼	8,5	▼	10,5	▼	12,6	▼	
	HMF 80E-K7											
	kg	3020	▼	1920	▼	1310	▼	940	▼	700	▼	
	m	4,7	▼	6,6	▼	8,5	▼	10,5	▼	12,6	▼	
	HMF 80E-K8											
	kg	2920	▼	1830	▼	1230	▼	870	▼	630	▼	
	m	4,8	▼	6,7	▼	8,6	▼	10,6	▼	12,7	▼	