DAF LF290 FA 4x2 - Special wide / low, Haken





Scanvo Trucks Danmark A/S Hårup Skovvej 7, Hårup 8600 Silkeborg

Sælger Salgsafdeling salg@scanvo.dk +45 8724 4370

+45 3046 2148 / 2498 2148 / 2497 2148

Basis	
Туре	Truck
Aksel	4x2
Stand	As now

Registration		
Model year	2022	
Reg. date	24-08-2022	
Reg. no.	DN21104	
Latest inspection	18-07-2023	
Chassis number (VIN)		
	XLRAEL2700L507741	
Ref. no.	7507	

Engine and transmission			
Engine		PX-7 217 K	
Нр		290	
Km		25000	
Gear box	AS Tronic 6	gear automatic	
EURO type		6	
Number of ta	nks	1	
Litre of tank		Ca. 200	
Ad-blue		✓	
Adblue litre o	f tank	50	
Without clutc	h pedal	✓	

Fahrhaus ausen	
Color	Gul / Rød
additional worklights	✓
Blitz lights	✓

Cab	
Cab type	M-cab
Air-conditioning	✓
Mirror camera	✓
Rear-view camera	✓
Radio	₩
Walkie	✓
Navigation	✓
Lane-assistent	✓
Cab airheater	✓
Distance radar	✓
Cruise control	✓
Multifunction steering wheel	✓
Air in cabin for cleaning	✓
Remote reading of tachograph	✓
Bluetooth	
Automatic disaster Brake (FCW)	✓
Chassis	
Wheelbase mm	4200
Axle load, front kg	6000
Axle load, rear kg	10000
Chassis height mm	1220
Toolbox	₩
Closed sides	✓
Aluminium cover	✓
Tippers	
Rear tipper	✓

Tyres		
% remaining		50 - 50
Dimensions	285/70R2	2,5 - 445/45R22,5
Brakes		
Disc brake		✓
ABS		✓
Engine brake		✓
Suspension		
Front, air		✓
Rear, air		ℯ
Dimensions		
External heigh	t mm	2700
External width	mm	2100
External length	n mm	Ca. 7000
Truck bed heig	ıht mm	1220
Weight		
Loading capaci	ty kg	8800
Overall weight	kg	16000
Tare weight kg		7200
Hook lift		
Make		Hiab
Type		ULT14S43 V - OFT
Serial number		U14S4312762621
Model year		2021
Removable ho	ok	✓
Max container messure mm 5220 & 5970 ved udskuds kofanger		

Beskrivelse

Special narrow and low city truck

DAF LF 290 4x2 FA Euro 6

Hiab 14 ton hook lift for variable box length from 4100 mm to 5220 mm - by using (750 mm) extension bumper the length can be increased to 5970 mm containers - height for rollers from ground is approx. 1220mm - internal locks in the back. tool box with drawers - chassis skirts and cubicle with lacquered aluminum door on top - Shovel and broom fittings

ACC distance rows - Lane departure system

Axle distance 4200 mm - Rearaxel Ratio 4.1 - full air suspension with dump function - 6-speed automatic gearbox - oil burner - reversing camera - cyclist camera - flash light front + rear + sides - working lights in steps and to the sides and in the back.

The cab is a special design with folding mirror arms which makes it possible to achieve a width of only 2100 non-rand valovchaigh no fuse 2700 mm in addition

Special narrow rear axle with single mounted tire mounting which makes it possible to achieve the narrow width



















































































