





Scanvo Trucks Danmark A/S Hårup Skovvej 7, Hårup 8600 Silkeborg

Sælger Salgsafdeling salg@scanvo.dk +45 8724 4370 +45 3046 2148 / +45 2498 2148

THE RESERVE OF THE PARTY OF THE	
Registration	
Model year	2025
Chassis number (VIN)	0054
Ref. no.	7773
Brand new	✔
Basis	
Туре	Trailer
Aksel	4
Stand	Brand new
Tyres	
% remaining	100
Dimensions	235/75R17,5
Auto transport	
Platform length	8250 mm
Suspension	
Air	✓

Brakes	
Drum brakes	✓
ABS	✓
Weight	
Loading capacity kg	22260
Overall weight kg	30000
Tare weight kg	7740
Total weight, low loader kg	44000
Load capacity, low loader kg	36260
Low loader	
Outriggers with planks	<b>√</b>
Double ramp	₩
Hydraulic ramps	<b>√</b>
Wide load signs	✓
Truck body / box	
Bottom 70 mm træplanker, rifle	et stålbund
Lashing rings in the bottom	₩

Coupling	
Brand	VBG 57 mm
Air-coupling	Duomatic
Variable drawbar	ja
Coupling height mm	800
Dimensions	
Internal length mm 545	0 + 2850mm på repo
Width mm	2550
Load highness at side	mm1080mm på rapo
Truck bed height mm	900
Chassis	
Toolbox	✓
Total length mm	9950-10550mm
Shaft type	BPW
Axle load kg	11 + 11 + 11 + 11

## Beskrivelse

New Hangler VTS-H 400 4-axle machine trailer - double ramps

Total bed length 8250 mm bed length - 2000 + 850 mm on platform - 4600 mm flat section + 850 mm inclined section Fully galvanized chassis and ramps

hydraulic galvanized ramps 2-part ramp L 2800mm + 800 mm - W 750mm - via the front vehicle's hydraulics, you can raise/lower and side shift the ramps, which are operated by handles on the side. Furthermore, the hydraulic system has a throttle valve installed so that the pressure can be adjusted manually

(alternatively, when ordering, the trailer can also be delivered as a single full ramp and with a 24 volt power plug / hydraulic station instead)

BPW 11 ton axles with drum brakes and air suspension with raise/lower function

235/75R17.5 tires mounted with M+S approved pattern

70 mm wooden planks in bottom, and grooved steel above the wheel arches - 2 x 5 pcs. stick holes in edge rail - 2 x 8 pcs. 10 ton lashing eyes in edge rail - 2 pcs. 5 ton at the front - low loading height of 900 mm - Extra 70mm for widening planks which are located in the middle recessed in the bottom of the flat

Storage magazine for chains / straps built into rapo

sliding drawbar with 57 mm towing eye, minimum coupling length 9950 mm can be increased by 600 mm stainless tool box

LED 3 chamber rear lights

4 pcs. extendable wide load signs with reflex planks and LED position lights to 3000 mm

4 pcs. LED work lights (2 pcs. on the side + 2 pcs. at the back)

Removable rotating beacon on one ramp

Approved for block truck driving 60 km/h: 44,000 kg / load 36,260 kg - at 90 km/h: 30,000 kg / load 22,260 kg

Reservations for printing and typing errors - ready for delivery end of September 2025

- AN OFFER YOU CAN'T REFUSE

We always have a wide selection of new and used units - Call for more information about delivery time can also be delivered as a single complete ramp - - Contact us today at +45 8724 4370 to hear more!

some of the toughest tasks. The product range ranges widely - from machine, low-mounted, heavy-duty or curtain trailers, trailers, etc. You will receive a well-equipped product for the tough tasks that are often performed in the Scandinavian and Nordic countries.









































